

Features

- Hybrid protection technology
- Extremely low leakage current
- Heavy duty surge protection
- LED indicators and audible alarm
- Compact form factor
- Indoor or outdoor installation

- UL1449 5th Edition
- RoHS compliant*

1251 Series – Hardwired AC Hybrid Surge Protective Device (H-SPD)

General Information

The Bourns® Model 1251 Series is a Type 1 hardwired hybrid surge protective device targeted for AC infrastructure applications. The hybrid Model 1251 design combines fast responding MOV technology with low leakage GDT technology resulting in reliable and long term performance.

Additional Information

Click these links for more information:











LIBRARY

TECHNICAL INVENTORY

Electrical Characteristics

		Model No.		
Characteristic		1251-120S	1251-208Y	1251-240S
Electrical Distribution System		120 VAC Single Ph	120 / 208 VAC 3 Ph Wye	120 / 240 VAC Single Ph
Nominal (Operating) Voltage		120 VAC	120 / 208 VAC	120 / 240 VAC
Maximum Operating Voltage	MCOV	150 VAC		
Temporary Overvoltage Withstand	U _T	150 VAC		
Nominal Discharge Current in 15 Applications of 8/20 μ s Impulse Waveform	In	20 kA		
Maximum Discharge Current 8/20 μs Withstand Single Operation	I _{max}	50 kA		
Overvoltage Protection Rating (3 kA)	V _{pr}	700 VAC		
Protection Level at In	U _p -I _n	1200 VAC		
Short Circuit Current Rating	I _{sccr}	100 kA		

Disconnection Features / Options

Thermal Disconnect	Internal
Fuses or Circuit Breakers	40 A
Ground Fault Breaker (if Installed) .	Type S or Delay

Mechanical Characteristics

Enclosure	Aluminum
Environmental Rating	IP 66 / NEMA 4x
Operating Temperature	40 °C to +85 °C
Mounting	Bulkhead (3/4)
Weight	2.5 lbs.
Disconnection Indicator	LED off and audible alarm on
Electrical Connection	12 AWG wiring leads, 20 inches max. length
Mechanical Connection to Panel	12 gauge, straight nipple with conduit nut
	for mounting through 0.5 inch knockout
	(actual hole size 0.875 inch)

Standards Compliance

UL1449 5th Edition, Type 1	E313168
, , , ,	Low Voltage SPD - Test Class II
EN 61643-11. Europe	Low Voltage SPD - Test Class II

How To Order

1251 - xxxx - xx

Series Nominal (Operating) Voltage

120S = 120 VAC 208Y = 120/208 VAC 240S = 120/240 VAC

Configuration -

N1= Wiring/Nipple Right Side Exit N2 =Wiring/Nipple Rear Exit

Packaging Specifications

1251 Seriesone unit per box

Agency Listing

Agency	Category	Agency File No.
CUL US	UL1449 - 5th Ed.	E313168

Specifications are subject to change without notice.

^{*}RoHS Directive 2015/863, Mar 31, 2015 and Annex.

Applications


- Service entrance, branch and OEM panels
- Electrical infrastructures
- Equipment and systems
- Protection from lightning
- Protection from AC power-induced problems


1251 Series – Hardwired AC Hybrid Surge Protective Device (H-SPD)

BOURNS


Product Dimensions


N1 Configuration






N2 Configuration







DIMENSIONS: MM

BOURNS®

Americas: Tel: +1 951-781-5500 • Email: americus@bourns.com
Mexico: Tel: +52-614-478-0400 • Email: mexicus@bourns.com
Asia: Tel: +886-2-2562-4117 • Email: asiacus@bourns.com
EMEA: Tel: +36 88 885 877 • Email: eurocus@bourns.com

www.bourns.com

REV. 06/25

Legal Disclaimer Notice

BOURNS

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: http://www.bourns.com/legal/disclaimers-terms-and-policies

PDF: http://www.bourns.com/docs/Legal/disclaimer.pdf