

Features

- Leadless, surface mount for economical assembly
- Compact mini-size
- Low capacitance and insertion loss
- RoHS compliant*
- **TAN**® UL Recognized

2055 Series Gas Discharge Tube Surge Protector

Bourns offers a low-cost surface mount (SM) 2-electrode GDT surge protection device. The 2055 Series is ideal for broadband protection due to its ultra-low capacitance. The 2055 Series offers superior protection characteristics suitable for telecommunications, commercial and industrial applications.

Additional Information

Click these links for more information:











LIBRARY

Characteristics

Test Methods per ITU-T (CCITT) K.12 and IEEE C62.31

| Characteristic | Model No. | | | | | |
|-------------------------------|-----------|------------------|---------|---------|---------|--|
| Characteristic | 2055-07 | 07 2055-09 2055- | 2055-23 | 2055-25 | 2055-30 | |
| DC Sparkover ± 20 % @ 100 V/s | 75 V | 90 V | 230 V | 250 V | 300 V | |
| Impulse Sparkover (1) | | | | | | |
| 100V/μs | 600 V | 600 V | 450 V | 450 V | 500 V | |
| 1000V/μs | 700 V | 700 V | 550 V | 550 V | 600 V | |

| Characteristic | Model No. | | | | |
|-------------------------------|-----------------|---------|---------|---------|--|
| Characteristic | 2055-35 2055-40 | 2055-40 | 2055-60 | 2055-80 | |
| DC Sparkover ± 20 % @ 100 V/s | 350 V | 400 V | 600 V | 800 V | |
| Impulse Sparkover (1) | | | | | |
| 100V/μs | 600 V | 600 V | 800 V | 1000 V | |
| 1000V/μs | 750 V | 700 V | 900 V | 1200 V | |

⁽¹⁾ Impulse Sparkover voltage is defined as typical values of distribution.

| Insulation Resistance (IR) | . 50V / 100 V ⁽²⁾ | > 10 ¹⁰ Ω |
|-------------------------------|------------------------------|----------------------|
| | . 10 mA | |
| Arc Voltage | .>2 A | ~ 12 V |
| Glow-Arc Transition Current | | <1 A |
| Capacitance | . 1 MHz | 1.0 pF maximum |
| DC Holdover Voltage (3) | .>150 V | < 150 ms |
| Impulse Discharge Current | . 5000 A, 8/20 μs | 10 operations |
| | 100 A, 10/1000 μs | > 300 operations |
| | 10 A, 10/1000 μs | > 1500 operations |
| Alternating Discharge Current | . 10 Arms, 9 cycles | 1 operation min. |
| | 2.5 Arms, 1 sec, 50 Hz | |
| Operating Temperature | | 40 to +85 °C |
| | | |
| ESD Classification (HBM) | | 6 |

Notes:

- UL Recognized component, UL File E153537.
- · At delivery AQL 0.65 Level II, DIN ISO 2859.
- Surface Mount (SM) parts may show a temporary increase in DCBD after the solder reflow process. Most devices will recover within 24 hours time. It should be noted that there is no quality defect nor change in protection levels during the temporary change in DCBD.
- · Bourns recommends reflowing surface mount devices per IPC/JEDEC J-STD-020 rev D.

(2) Insulation Resistance test conditions:

DC Sparkover **DC Measuring Voltage Voltage** 75 - 150 V..... ≥151 V


(3) Network applied.



2055 Series Gas Discharge Tube Surge Protector

BOURNS


Product Dimensions




DIMENSIONS: MILLIMETERS

Packaging Specifications


The Model 2055-xx-SM ships standard reelpack (-RP), 800 pieces per reel, 2,400 pieces per box. Reel is 330 mm in diameter and 16 mm wide.



Recommended Pad Layout



How to Order



LF = RoHS Compliant Product

BOURNS®

Asia-Pacific: Tel: +886-2 2562-4117 • Email: asiacus@bourns.com

EMEA: Tel: +36 88 885 877 • Email: eurocus@bourns.com

The Americas: Tel: +1-951 781-5500 • Email: americus@bourns.com

www.bourns.com

Legal Disclaimer Notice



This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., ISO/TS 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: http://www.bourns.com/legal/disclaimers-terms-and-policies

PDF: http://www.bourns.com/docs/Legal/disclaimer.pdf