

Features

- Power from 10 to 60 W
- Output voltage from 3.3 to 12 V
- Hi-Pot up to 1500 VAC
- Surface mount
- RoHS compliant*

Applications

- High efficiency PoE interface and DC-DC controllers
- PoE PD controllers
- Synchronous flyback converters

PDC-FD Series – DC to DC Transformers

General Specifications

Operating Temperature.....	-40 °C to +125 °C
Storage Temperature.....	-40 °C to 85 °C
Moisture Sensitivity Level.....	1

Additional Information

Click these links for more information:



Electrical Specifications @ 25 °C

Bourns Part Number	Primary Inductance		Leakage Inductance		DC Resistance @ 0.3 V		Turns Ratio @ 100 kHz, 0.1 V _{rms} ¹		Hi-Pot	
	Primary Terminals	Value	Primary Terminals	Value	Primary Terminals	Value	Primary Terminals	Value	Primary Terminals	Value
PDC010-FD15A03S	(3-5) @ 100 kHz, 0.1 V _{rms}	166.5 μH ±10 %	(3-5) w/ (7-8, 9,10-11,12 shorted) @ 250 kHz, 0.1 V _{rms}	2.5 μH max.	(1-2)	720 mΩ max.	(3-5:2-1)	2 ±2 %	(2,3-11,12) @ 2 mA, 1 sec.	1500 VAC ref.
				0.4 μH max.	(3-5)	765 mΩ max.	(3-5:8-7)	3.7 ±2 %		
			(7-8) w/ (9,10-11,12 shorted @ 250 kHz, 0.1 V _{rms}		1.5 μH max.	(7-8)	380 mΩ max.	(3-5:11,12-9,10)		
				(9,10-11,12)		20 mΩ max.				
PDC015-FD15A05S	(1,2-3,4) @ 250 kHz, 0.1 V _{rms}	95 μH ±10 %	(1,2-3,4) Other terminals shorted @ 100 kHz, 0.1 V _{rms}	1.5 μH max.	(1,2-3,4)	230 mΩ max.	(1-3:2-4)	1.0 ±2 %	(1,2,5-10,11,12) @ 2 mA, 1 sec.	1500 VAC ref.
					(5-6)	375 mΩ max.	(1-3:5-6)	2.25 ±2 %		
					(7,8,9-10,11,12)	10 mΩ max.	(1-3:10,11,12- 7,8,9)	5.4 ±2 %		
PDC020-FD15A12S	(3,4-5,6) @ 250 kHz, 0.1 V _{rms}	200 μH ±10 %	(3,4-5,6) w/ (9,10- 11,12 shorted) @ 250 kHz, 0.1 V _{rms}	1.8 μH max.	(3,4-5,6)	200 mΩ max.	(3,4-5,6:2-1)	4.0 ±2 %	(2,3,4-8,11,12) @ 5 mA, 1 sec.	1500 VAC ref.
				5.8 μH max.	(9,10-11,12)	35 mΩ max.	(3,4-5,6:7-8)	6.66 ±2 %		
			(3,4-5,6) w/ (7-8 shorted) @ 250 kHz, 0.1 V _{rms}		1.0 μH max.	(1-2)	250 mΩ max.	(3,4-5,6:12,11- 9,10)		
				(8-7)		160 mΩ max.				
PDC025-FD20A05S	1 - 3 (1,2 short 3,4 short) @ 250 kHz, 0.5 V _{rms}	70 μH ±10 %	(1-3) w/ (1,2 short 3,4 short 5,6 short 7,8, 9,10,11,12 short) @ 250 kHz, 0.5 V _{rms}	1.0 μH max.	(1-3) w/ (1,2 short 3,4 short)	70 mΩ max.	(1-3:5-6) w/ (1,2 short 3,4 short 7,8, 9 short 10,11,12 short)	2.444 ±5 %	(5-1) w/ (1,2 short 3,4 short 7,8, 9 short 10,11,12 short) @ 1mA, 2 sec.	1500 VAC ref.
					(12-7)	20 mΩ max.				
					(11-8)		310 mΩ max.			
					(10-9)					
					(5-6)					

¹ Turn ratio condition of PDC025-FD20A05S is 250 kHz, 0.5 V_{rms}, other part numbers are 100 kHz, 0.1 V_{rms}

(Continued)



CALIFORNIA WARNING: Can expose you to lead, a carcinogen and reproductive toxicant.
See www.P65Warnings.ca.gov

*RoHS Directive 2015/863, Mar 31, 2015 and Annex.
Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

PDC-FD Series – DC to DC Transformers




Electrical Specifications @ 25 °C (continued)

Bourns Part Number	Primary Inductance		Leakage Inductance		DC Resistance @ 0.3 V		Turns Ratio @ 100 kHz, 0.1 V _{rms} ¹		Hi-Pot	
	Winding	Value	Winding	Value	Winding	Value	Winding	Value	Winding	Value
PDC025-FD20A12S	(3,4-5,6) @ 250 kHz, 0.1 V _{rms}	75 μH ±10 %	(3,4-5,6) w/ (9,10,11,12 shorted) @ 250 kHz, 0.1 V _{rms}	0.76 μH max.	(3,4-5,6)	77 mΩ max.	(3,4-5,6:12,11-9,10)	4.0 ±2 %	(2,3,4-8,11,12) @ 5 mA, 2 sec.	1500 VAC ref.
					(9,10-11,12)	9.8 mΩ max.	(3,4-5,6:2-1)	4.0 ±2 %		
					(1-2)	96 mΩ max.	(3,4-5,6:8-7)	6.66 ±2 %		
					(8-7)	70 mΩ max.				
PDC060-FD20A12S	(1,2-3,4) @ 200 kHz, 1.0 V _{rms}	20.5 μH ±5 %	(1,2-3,4) w/ (5,6,7,8,9,10,11,12 shorted) @ 100 kHz, 1.0 V _{rms}	1.0 μH max.	(1,2-3,4)	45 mΩ max.	(1,2-3,4:10,11,12-7,8,9)	2.67 ±5 %	(1,2,5-10,11,12) @ 1 mA, 2 sec.	
					(10,11,12-7,8,9)	12 mΩ max.	(1,2-3,4:5-6)	2.28 ±5 %		
					(5-6)	250 mΩ max.				

¹ Turn ratio condition of PDC025-FD20A05S is 250 kHz, 0.5 V_{rms}, other part numbers are 100 kHz, 0.1 V_{rms}

Solder Profile



IR Reflow Profile		Pb-Free Assembly
Step #	Profile Feature	Condition / Duration
Step 1	Ramp Up Rate	3 °C / second max.
Step 2	Preheat 150 °C to 200 °C (T _a to T _b)	t1-t2: 60-120 seconds
Step 3	Ramp Up Rate (T _L to T _P)	3 °C / second max.
	Temperature Maintained Above 217 °C	60-150 seconds
Step 4	Peak Temperature (T _P)	260 +0/-5 °C
	Time Within 5 °C of Actual Peak Temperature	30 seconds max.
Ramp Down Rate (T _P to T _L)		6 °C/second max.

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.


The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

PDC-FD Series – DC to DC Transformers


BOURNS®

Product Dimensions


PDC010-FD15A03S, PDC015-FD15A05S, PDC020-FD15A12S



PDC025-FD20A05S, PDC025-FD20A12S



PDC060-FD20A12S



DIMENSIONS: $\frac{\text{MM}}{\text{(INCHES)}}$

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.


The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

PDC-FD Series – DC to DC Transformers


BOURNS®

Electrical Schematics


PDC010-FD15A03S




PDC015-FD15A05S




PDC020-FD15A12S




PDC025-FD20A05S



PDC025-FD20A12S




PDC060-FD20A12S




Recommended Layout


PDC010-FD15A03S, PDC015-FD15A05S, PDC020-FD15A12S



PDC025-FD20A05S, PDC025-FD20A12S, PDC060-FD20A12S



How To Order



Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.




The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

PDC-FD Series – DC to DC Transformers

BOURNS®

Packaging Specifications

PDC010-FD15A03S, PDC015-FD15A05S, PDC020-FD15A12S: 200 pcs./reel, 2 reels/carton, 400 pcs.



DIMENSIONS: $\frac{\text{MM}}{\text{(INCHES)}}$

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.




The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

PDC-FD Series – DC to DC Transformers

BOURNS®

Packaging Specifications

PDC025-FD20A05S, PDC025-FD20A12S: 150 pcs./reel, 2 reels/carton, 300 pcs.



DIMENSIONS: $\frac{\text{MM}}{\text{(INCHES)}}$

PDC060-FD20A12S: 40 pcs./tray, 4 trays/inner box, 6 inner boxes/carton, 960 pcs.

BOURNS®

Asia-Pacific: Tel: +886-2 2562-4117 • Email: asiacus@bourns.com

Europe: Tel: +36 88 885 877 • Email: eurocus@bourns.com

Mexico: Tel: +52 614 478 0400 • Email: mexicus@bourns.com

The Americas: Tel: +1-951 781-5500 • Email: americus@bourns.com

www.bourns.com

REV. 02/26

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:

Web Page: <http://www.bourns.com/legal/disclaimers-terms-and-policies>

PDF: <http://www.bourns.com/docs/Legal/disclaimer.pdf>