


MATERIAL DECLARATION SHEET



Material Number	3313 (26KΩ to 2MΩ)			
Product Line	Trimmer			
Compliance Date	3-8-2005			
RoHS Compliant	Yes DC 510	MSL	1	

Construction Element (Subpart)	Homogeneous Material	Material Weight (g)	Homogeneous Material	CASRN	Material Mass %	Material Mass % of total unit wt.	Subpart mass of total wt. (%)
			Substance				
Contact Spring	Ni/Ag	0.0009	Nickel	7440-02-0	18	0.133	0.74
			Copper	7440-50-8	65	0.481	
			Zinc	7440-66-6	17	0.126	
Rotor	Nylon	0.074	Liquid Crystal Polymer	70679-92-4	60	36.513	60.86
			Glass Fiber	65997-17-3	40	24.342	
Seal Ring	Rubber	0.0001	Silicon Rubber	112926-00-8	100	0.082	0.08
Housing	Nylon	0.0125	Polyamide 46	32131-17-2	39.5	4.060	10.28
			Glass Fiber	65997-17-3	40	4.112	
			Antimony Trioxide	1309-64-4	5.5	0.565	
			Tribromopolystyrene	57137-10-7	15	1.542	
Lead Frame	Copper Alloy	0.0117	Copper	7440-50-8	100	9.622	10.44
	Plating	0.001	Tin	7440-31-5	100	0.822	
Substrate	Ceramic	0.019	Aluminum Oxide	1344-28-1	96	15.000	15.63
			Silicon Dioxide	7631-86-9	2	0.313	
			Magnesium Oxide	1309-48-4	1	0.156	
			Calcium Oxide	1305-78-8	1	0.156	
Termination Ink	Ink	0.0004	Silver	7440-22-4	50.5	0.166	0.33
			Palladium	7440-05-3	34.1	0.112	
			Platinum	7440-06-4	3.1	0.010	
			Manganese	7439-96-5	1	0.003	
			Bismuth	7440-69-9	8.9	0.029	
			Boron	7440-42-8	1.5	0.005	

MATERIAL DECLARATION SHEET



Resistive Ink	Ink	0.0015	Silicon	7440-21-3	0.9	0.003	1.23
			Ruthenium Dioxide	12036-10-1	20	0.247	
			Boron	7440-42-8	13	0.160	
			Silicon	7440-21-3	42	0.518	
			Lead	7439-92-1	24	0.296	
Lubricant	Lube	0.0005	Polydimethylsiloxane	63148-62-9	24	0.099	0.41
			Silica, Amorphous	7631-86-9	3	0.012	
			Siloxane/Silicones	63148-56-1	73	0.300	
Total Weight		0.1216					

This Document was updated on: 7-3-2019

Important remarks:

1. It is the responsibility of the user to verify they are accessing the latest version.
2. RoHS exemption used –7(c)-I Electrical and electronic components containing lead in a glass or ceramic...
3. Halogen Free Model available GK2 version for single-slot rotor and GL5 for cross-slot rotor