

MATERIAL DECLARATION SHEET

BOURNS®

Material Number	PF-63R50H-X, PF-63R50H-L, PF-63R50H-XL series			
Product Line	Power Fuses			
Compliance Date	2025/2/11			
RoHS Compliant	Yes	MSL	1	

No.	Construction Element(subpart)	Homogeneous Material	Material weight [g]	Homogeneous Material\ Substances	CASRN if applicable	Materials Mass %	Material Mass % of total unit wt.	Subpart mass of total wt. (%)
1	Ceramic tube	Ceramic	1.943	Aluminum oxide	1344-28-1	94.226%	48.49	51.462
				Silicon dioxide	7631-86-9	4.94%	2.542	
				Zirconium dioxide	1314-23-4	0.834%	0.429	
2	Cap	Copper alloy	0.3616	Copper	7440-50-8	64.39%	6.167	9.587
				Zinc	7440-66-6	35.60%	3.409	
				Iron	7439-89-6	0.01%	0.001	
		Plating Nickel	0.0004	Nickel	7440-02-0	100.00%	0.010	
3	Cap (outer)	Copper alloy	0.3956	Copper	7440-50-8	64.39%	6.746	10.487
				Zinc	7440-66-6	35.60%	3.729	
				Fe	7439-89-6	0.01%	0.001	
		Plating Nickel	0.0004	Nickel	7440-02-0	100.00%	0.01	
4	Tinned copper wire	Copper	0.5939	Copper	7440-50-8	100.00%	15.722	15.726
		Plating Tin	0.0001	Tin	7440-31-5	100.00%	0.003	
5	Silica Sand	Quartz	0.410	Quartz	14808-60-7	100.00%	10.858	10.858
6	Fuse element	Copper	0.070	Copper	7440-50-8	100.00%	1.854	1.854

MATERIAL DECLARATION SHEET

BOURNS®

7	Ink	Ink	0.001	Acrylate	/	12.00%	0.003	0.026
				Aluminum	7429-90-5	38.00%	0.008	
				Pentaerythritol Triacrylate	3524-68-3	38.00%	0.008	
				3- Glycidoxypropyltrimethoxysilane	2530-83-8	12.00%	0.003	
		Total Weight	3.776					

This Document was updated on: 2025/02/11

Important remarks: It is the responsibility of the user to verify they are accessing the latest version.