




















Bourns® Multifuse® Product Guide

SURFACE MOUNT POLYMER PTCs







Model Series	Photo	Technology	Mounting Configuration	Footprint	Voltage Rating	Hold Current (Amps)	Certifications
MF-ASML/X		Low Resistance Polymer PTC	SMD	0402 / 1005	6 Vdc	0.10 – 0.50	UL, CSA, TÜV
MF-FSMF		Polymer PTC	SMD	0603 / 1608	6 Vdc – 15 Vdc	0.10 – 0.50	UL, CSA, TÜV
MF-FSML/X		Low Resistance Polymer PTC	SMD	0603 / 1608	6 Vdc – 8 Vdc	0.35 – 3.00	UL, CSA, TÜV
MF-FSHT		High Temperature Polymer PTC	SMD	0603 / 1608	12 Vdc	0.05 – 0.16	UL, CSA, TÜV
MF-PSMF		Polymer PTC	SMD	0805 / 2012	6 Vdc – 24 Vdc	0.10 – 1.10	UL, CSA, TÜV
MF-PSML/X		Low Resistance Polymer PTC	SMD	0805 / 2012	6 Vdc – 12 Vdc	0.75 – 4.50	UL, CSA, TÜV
MF-PSHT		High Temperature Polymer PTC	SMD	0805 / 2012	12 Vdc – 16 Vdc	0.05 – 0.50	UL, CSA, TÜV, AEC-Q200
MF-NSMF		Polymer PTC	SMD	1206 / 3216	6 Vdc – 30 Vdc	0.12 – 2.00	UL, CSA, TÜV, AEC-Q200
MF-NSML/X		Low Resistance Polymer PTC	SMD	1206 / 3216	6 Vdc – 12 Vdc	1.50 – 6.00	UL, CSA, TÜV
MF-NSHT		High Temperature Polymer PTC	SMD	1206 / 3216	12 Vdc – 30 Vdc	0.16 – 0.35	UL, CSA, TÜV, AEC-Q200
MF-USMF		Polymer PTC	SMD	1210 / 3225	6 Vdc – 30 Vdc	0.05 – 1.75	UL, CSA, TÜV, AEC-Q200
MF-USML/X		Low Resistance Polymer PTC	SMD	1210 / 3225	6 Vdc – 12 Vdc	1.75 – 7.00	UL, CSA, TÜV
MF-USHT		High Temperature Polymer PTC	SMD	1210 / 3225	12 Vdc – 30 Vdc	0.10 – 0.50	UL, CSA, TÜV, AEC-Q200
MF-MSMF		Polymer PTC	SMD	1812 / 4532	6 Vdc – 60 Vdc	0.10 – 3.00	UL, CSA, TÜV, AEC-Q200
MF-MSHT		High Temperature Polymer PTC	SMD	1812 / 4532	9 Vdc – 42 Vdc	0.20 – 1.75	UL, CSA, TÜV, AEC-Q200
MF-SMDF		Polymer PTC	SMD	2018 / 5146	10 Vdc – 60 Vdc	0.30 – 2.60	UL, CSA, TÜV
MF-LSMF		Polymer PTC	SMD	2920 / 7555	6 Vdc – 33 Vdc	1.85 – 4.00	UL, CSA, TÜV, AEC-Q200
MF-GSMF		Polymer PTC	SMD	3425 / 8764	36 Vdc	3.00	UL, CSA, TÜV
MF-SM		Polymer PTC	SMD	2920 – 3425 / 7555 – 8764	6 Vdc – 60 Vdc	0.30 – 3.00	UL, CSA, TÜV
MF-SMHT		High Temperature Polymer PTC	SMD	2920 – 3425 / 7555 – 8764	16 Vdc	1.36 – 1.60	AEC-Q200
MF-SM/250		High Power Rating Polymer PTC	SMD	3425 / 8764	60 Vdc / 250 Vac	0.08 – 0.13	UL, CSA, TÜV
MF-SM/250V		High Power Rating Polymer PTC	SMD	Refer to Data Sheet	60 Vdc / 250 Vac	0.13	UL, CSA, TÜV
MF-SD/250		High Power Rating Polymer PTC	SMD	Refer to Data Sheet	60 Vdc / 250 Vac	0.13	UL, CSA

Bourns® Multifuse® Product Guide



RADIAL LEADED POLYMER PTCs

Model Series	Photo	Technology	Mounting Configuration	Voltage Rating	Hold Current (Amps)	Certifications
MF-R		Polymer PTC	Radial Leaded Through-hole	16 Vdc – 60 Vdc	0.05 – 11.00	UL, CSA, TÜV
MF-RG		Polymer PTC	Radial Leaded Through-hole	16 Vdc	3.00 – 11.00	UL, CSA, AEC-Q200
MF-RHT		High Temperature Polymer PTC	Radial Leaded Through-hole	16 Vdc – 32 Vdc	0.50 – 13.00	UL, CSA, AEC-Q200
MF-RM		High Power Rating Polymer PTC	Radial Leaded Through-hole	240 Vdc / 265 Vac	0.05 – 0.55	UL, CSA, TÜV
MF-RX/72		Polymer PTC	Radial Leaded Through-hole	72 Vdc	0.20 – 3.75	UL, CSA, TÜV
MF-RX/250		High Power Rating Polymer PTC	Radial Leaded Through-hole	60 Vdc / 250 Vac	0.12 – 0.18	UL, CSA, TÜV

STRAP POLYMER PTCs

Model Series	Photo	Technology	Mounting Configuration	Voltage Rating	Hold Current (Amps)	Certifications
MF-LR		Low Resistance Polymer PTC	Strap	10 Vdc – 20 Vdc	1.9 – 9.0	UL, CSA, TÜV
MF-LS		Polymer PTC	Strap	15 Vdc – 24 Vdc	1.8 – 3.4	UL, CSA, TÜV
MF-S		High Temperature Polymer PTC	Strap	15 Vdc – 30 Vdc	1.2 – 4.2	UL, CSA, TÜV
MF-SVS		Polymer PTC	Strap	10 Vdc	1.7 – 2.7	UL, CSA, TÜV
MF-VS		Polymer PTC	Strap	16 Vdc	1.7 – 2.1	UL, CSA, TÜV
MF-VS Narrow Body		Polymer PTC	Strap	12 Vdc	1.7 – 2.1	UL, CSA, TÜV

CUSTOMIZED POLYMER PTCs

Model Series	Photo	Technology	Mounting Configuration	Voltage Rating	Hold Current (Amps)	Certifications
MF-D		Polymer PTC	Clamp	15 Vdc	2.5 – 12.2	Available upon request
MF-DC		Polymer PTC	Clamp	16 Vdc	50	Available upon request

www.bourns.com

"Bourns" and "Multifuse" are registered trademarks of Bourns, Inc. in the United States and other countries.
Copyright © 2021, Bourns, Inc. • Litho in USA • MIMEO • 92/21 • e/MF2106

BOURNS®